



PREMIUM BIG SCREEN LCD CCTV MONITOR

Spec		42RTH
Display	Screen Size	42"(Full HD)
	Viewing Area	930.24 x 523.26 mm
	Pixel Type	Active Matrix TFT
	Max. Resolution	1920 x 1080 @60Hz
	Pixel Pitch	0.4845 x 0.4845 mm
	Brightness	550cd/m ²
	Contrast Ratio	1600:1
	Aspect Ratio	16 : 9
	Viewing Angle(H/V)	178°/178°
	Display Color	16.7 Million
	Response Time	< 8ms
	Video System	NTSC / PAL
	Frequency(H)	30 ~ 80 KHz(H)
	Frequency(V)	56 ~ 75 KHz(V)
Audio	Built in Speakers	Yes(2W X 2)
	Gradual Volume Increase	YES
Interface	Video In/ Out(BNC Type)	2 / 2
	S-Video In/ Out	1 / 1
	RGB In(15Pin D-Sub)	1
	Component	1
	DVI In/ HDMI In	1 / 1
	Audio In/ Out(RCA Type)	2 / 1
	PC Stereo In	1
Transmitter	Remote Control	Yes
Special Features	Multi Display Function	PIP / PBP
	Filter Type	3D Comfilter / DeInterlace
	LCD Protection Glass	Not Available
	Multi-lingual Language	English, Spanish, French, German, Italian, Portuguese, Nederland
	VESA™ DDC Compatible	Yes
Dimension	Outline Dimension(With Stand)	1060 x 725 x 305 mm
	Outline Dimension(Without Stand)	TBD
	Packaging Dimension	1305 x 880 x 385 mm
	Net Weight	31Kg (68.3lbs)
	Gross Weight	35Kg (77.2lbs)
Cabinet	Finish/Tilt Stand	Black/Yes
Mounts	VESA Mounts Size	(130 X 130) X634 mm (BS M8 x 16 mm Screw)
Warranty	Parts/ Labor	1 Year / 1 Year
	MTBF(Approx.)	50,000 Hours
Regulations		TUV-NRTL(=UL), CB, FCC(A), CE-Emc(LVD)
Power	Consumption : < On	<250W
	Electrical Ratings	AC100 ~ 240V(50/60Hz)
Circumstance	Operating Temperature	10 ~ 40°C / 50 ~ 104°F